

Claims

- [c1] (Amended, Once) A method for obtaining nuclear magnetic resonance measurements in a wellbore, comprising:
inducing a static magnetic field in a fluid sample, the static magnetic field being primarily inhomogeneous in the fluid sample;
applying an oscillating magnetic field to the fluid sample according to a preparation pulse sequence that comprises a J-edit pulse sequence for developing J modulation; and
acquiring the nuclear magnetic resonance measurements using a detection sequence, wherein the detection sequence comprises at least one 180-degree pulse.
- [c2] (Original) The method of claim 1, wherein the J modulation is based on a heteronuclear coupling.
- [c3] (Original) The method of claim 2, wherein the heteronuclear coupling is carbon-proton coupling.
- [c4] (Original) The method of claim 3, wherein the J-edit pulse sequence includes a variable delay and the applying and the acquiring are performed a plurality of times to provide a plurality of nuclear magnetic resonance measurements each with a different value for the variable delay.
- [c5] (Original) The method of claim 4, further comprising analyzing amplitudes of the plurality of nuclear magnetic resonance measurements as a function of the variable delay to provide J coupling information or relative abundance of carbon groups.
- [c6] (Original) The method of claim 5, wherein the analyzing comprises solving a set of linear equations or performing a Fourier transformation.
- [c7] (Original) The method of claim 5, further comprising determining types of hydrocarbons present in the fluid sample.
- [c8] (Original) The method of claim 4, further comprising analyzing amplitudes of the plurality of nuclear magnetic resonance measurements to derive a composition of the

fluid sample, wherein the analyzing is performed using a basis set of measurements obtained with standard samples having known compositions.

- [c9] (Original) The method of claim 4, further comprising deriving a J-modulation curve describing amplitudes of the plurality of nuclear magnetic resonance measurements as a function of the variable delay; and comparing the J-modulation curve with a basis set of standard J-modulation curves to derive a composition of the fluid sample, wherein the basis set of the standard J-modulation curves are obtained with standard samples having known compositions.
- [c10] (Original) The method of claim 1, wherein the fluid sample is located in an earth formation.
- [c11] (Original) The method of claim 1, wherein the fluid sample is removed from an earth formation by a formation tester.
- [c12] (Original) The method of claim 4, wherein the nuclear magnetic resonance measurements comprise proton signals.
- [c13] (Original) The method of claim 4, wherein the nuclear magnetic resonance measurements comprise carbon signals.
- [c14] (Original) The method of claim 1, wherein the preparation pulse sequence further comprises a signal enhancement pulse sequence.
- [c15] (Original) The method of claim 14, wherein the signal enhancement pulse sequence is a nuclear Overhauser enhancement pulse sequence or a magnetization transfer pulse sequence.
- [c16] (Original) The method of claim 1, wherein the J-edit pulse sequence includes a gated-decoupling pulse.
- [c17] (Amended, Once) A method for characterizing formation fluids, comprising:
disposing a nuclear magnetic resonance instrument in a borehole;

inducing a static magnetic field in a fluid sample in a region of interest, the static magnetic field being primarily inhomogeneous in the fluid sample;
applying an oscillating magnetic field to the fluid sample according to a preparation pulse sequence that comprises a J-edit pulse sequence for developing J modulation; and
acquiring nuclear magnetic resonance measurements using a detection sequence, wherein the detection sequence comprises at least one 180-degree pulse.

- [c18] (Original) The method of claim 17, wherein the region of interest is in an earth formation.
- [c19] (Original) The method of claim 17, wherein the region of interest is inside the nuclear magnetic resonance instrument.
- [c20] (Original) The method of claim 17, wherein the J-edit pulse sequence includes a variable delay and the applying and the acquiring are performed a plurality of times to provide a plurality of nuclear magnetic resonance measurements each with a different value for the variable delay.
- [c21] (Original) The method of claim 20, further comprising analyzing amplitudes of the plurality of nuclear magnetic resonance measurements as a function of the variable delay to provide J coupling information or relative abundance of carbon groups.
- [c22] (Original) The method of claim 21, further comprising determining hydrocarbon types in the fluid sample.
- [c23] (Original) The method of claim 20, further comprising analyzing amplitudes of the plurality of nuclear magnetic resonance measurements to derive a composition of the fluid sample, wherein the analyzing is performed using a basis set of measurements obtained with standard samples having known compositions.
- [c24] (Original) The method of claim 20, further comprising deriving a J-modulation curve describing amplitudes of the plurality of nuclear magnetic resonance measurements as a function of the variable delay; and comparing the J-modulation curve with a basis set of standard J-modulation curves to derive a composition of the fluid sample, wherein the

basis set of the standard J-modulation curves are obtained with standard samples having known compositions.

[c25] (Amended, Once) A method for determining with a downhole tool an oil-to-water ratio in a fluid sample, comprising:

obtaining a nuclear magnetic resonance data set representing protons attached to carbon-13 in the fluid sample;

deriving a hydrocarbon content from the nuclear magnetic resonance data set, taking into account a natural abundance of carbon-13;

acquiring a total nuclear magnetic resonance for all protons in the fluid sample, wherein the fluid sample is subject to a primarily inhomogeneous static magnetic field;

deriving a total hydrogen index from the total nuclear magnetic resonance measurement; and

deriving the oil-to-water ratio of the fluid sample from the hydrocarbon content and the total hydrogen index.

[c26] (Original) The method of claim 25, wherein the nuclear magnetic resonance data set is obtained by subtracting a first proton nuclear magnetic resonance measurement acquired with a J-edit pulse sequence from a second proton nuclear magnetic resonance measurement acquired without a J-edit pulse sequence.

[c27] (Amended, Once) A nuclear magnetic resonance instrument, comprising:

a housing adapted to move in a wellbore;

a magnet disposed in the housing adapted to induce a static magnetic field in a zone of interest, the static magnetic field being primarily inhomogeneous in the zone of interest;

an antenna assembly disposed in the housing, the antenna assembly adapted to induce an oscillating magnetic field in the zone of interest and to receive nuclear magnetic resonance signals; and

an electronic module including a memory to store instructions for performing a J-edit pulse sequence.

- [c28] (Original) The instrument of claim 27, wherein the housing is adapted to be lowered into the wellbore on an electric cable.
- [c29] (Original) The instrument of claim 27, wherein the housing forms part of a drilling tool assembly.
- [c30] (Original) The instrument of claim 27, wherein the housing forms part of a formation fluid sampling tool.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.